



## STANDARD

4 levels of removable grid shelves | Self-closing pivoting front doors with triple tempered glass | Interior in skinplate | Exterior in skinplate | Ventilated refrigeration | Vertical LED lighting | Two-way fan motors | Electronic temperature controller | Programmable automatic defrosting | Castors

## OPTIONS

Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



-21/-18 °C | 0/4 °C



Automatic



LED



230V | 1 Ph | 50 Hz




L1/M1 | 25 °C | 60% R.H.



Plug-in



R290 ECO Friendly

Operating temperature	-21/-18 °C   0/4 °C
Refrigerant (ref/GWP)	R290/3
Defrost	Electric
External dimensions (LxDxH) (mm)	588x593x1795
TDA - Total display area (m <sup>2</sup> )	0,44
Net volume (l)	108
Refrigerated shelf area (m <sup>2</sup> )	0,61
Insulation	PUR/H2O
Nominal power (W)	520
Electric current (A)	2,62
TEC - Total energy consumption (kWh/24h)	6,816   2,943
AEC - Annual energy consumption (kWh/annum)	2487,84   1074,20
Energy efficiency class*	

\* The information presented regarding the energy class (Energy Labeling regulation and Eco Design regulation) is only related to the standard models. For the energy class of the equipments with different options that involve elements of energy consumption and/or changes in the construction of the unit, please contact the manufacturer directly.

\*\* Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

