



STANDARD

Base in AISI 304 stainless steel | Display area in AISI 304 stainless steel | Exterior decoration in skinplate | GN1/1 containers with covers | Multiplexible | LED lighting | Electronic temperature controller | Water drain tap | Tilting front glass | Tempered glasses | Adjustable stainless steel feet | Water loading tap

OPTIONS

Quartz worktop | Exterior decoration in painted plate (RAL) | Exterior decoration in AISI 304 stainless steel | Sliding rear doors | Front glass anti-condensation system | Castors with brakes | Adjustable stainless steel high feet | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



65/75 °C



Automatic



LED



230V | 1 Ph | 50 Hz



3 | 25 °C | 60% R.H.



Plug-in



R290 ECO Friendly

C101 VA 70H**150****200**

Operating temperature	65/75 °C	65/75 °C
Refrigerant (ref/GWP)	R290/3	R290/3
Defrost	Time	Time
External dimensions (LxDxH) (mm)	1545x1101x1254	1990x1101x1254
TDA - Total display area (m ²)	1,09	1,40
Net volume (l)	4 x GN 1/1	5 X GN 1/1
Insulation	PUR/H2O	PUR/H2O
Nominal power (W)	3214	4036
Electric current (A)	13,97	17,54

* Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

