



STANDARD

3 levels of removable, adjustable, and tiltable shelves | Sliding front doors with double tempered glass | Display area in skinplate | Front decoration in painted plate (RAL) | Acrylic product stopper | Full vision sides with double tempered glass | Multiplexible | Ventilated refrigeration | LED top lighting | Electronic temperature controller | Programmable automatic defrosting | Electric evaporation of defrost water | Adjustable feet

OPTIONS

Upper sling bar for hooks | Display area in painted plate (RAL) | Display area in AISI 304 stainless steel | Exterior decoration in painted plate (RAL) | Exterior decoration in AISI 304 stainless steel | Treated evaporator | LED lighting on shelves | Mirrored interior sides | Joining kit | Castors with brakes | Sliding condenser unit for maintenance | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



0/4 °C



Automatic



LED



230V | 1 Ph | 50 Hz




M1 | 25 °C | 60% R.H.



Plug-in



R290 ECO Friendly

HYSO PC 16	130	190	250
Operating temperature	0/4 °C	0/4 °C	0/4 °C
Refrigerant (ref/GWP)	R290/3	R290/3	R290/3
Defrost	Tempo	Tempo	Tempo
External dimensions (LxDxH) (mm)	1300x717x1600	1900x717x1600	2500x717x1600
TDA - Total display area (m²)	1,77	2,34	2,92
Net volume (l)	353	529	706
Refrigerated shelf area (m²)	1,95	2,93	3,90
Insulation	PUR/H2O	PUR/H2O	PUR/H2O
Nominal power (W)	559	825	1111
Electric current (A)	3,21	4,52	6,42
TEC - Total energy consumption (kWh/24h)	6,234	7,851	9,701
AEC - Annual energy consumption (kWh/annum)	2275,41	2865,62	3540,87
Energy efficiency class*			

* The information presented regarding the energy class (Energy Labeling regulation and Eco Design regulation) is only related to the standard models. For the energy class of the equipments with different options that involve elements of energy consumption and/or changes in the construction of the unit, please contact the manufacturer directly.

** Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

