



STANDARD

2 levels of removable, adjustable, and tiltable shelves | Sliding door with double glass | Display area in skinplate | Exterior decoration in skinplate | Panoramic sides with double tempered glass | Multiplexible | Ventilated refrigeration | LED top lighting | Electronic temperature controller | Programmable automatic defrosting | Automatic evaporation of defrost water | Adjustable feet

OPTIONS

Display area in painted plate (RAL) | Display area in AISI 304 stainless steel | Exterior decoration in painted plate (RAL) | Exterior decoration in AISI 304 stainless steel | Treated evaporator | LED lighting on shelves | Additional shelf without lighting | Mirrored glass sides | Joining kit | Castors with brakes | Adjustable stainless steel high feet | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



0/4 °C



Automatic



LED



230V | 1 Ph | 50 Hz



M1 | 25 °C | 60% R.H.



Plug-in



R290 ECO Friendly

L080 PC A	100	130	150	200
Operating temperature	0/4 °C	0/4 °C	0/4 °C	0/4 °C
Refrigerant (ref/GWP)	R290/3	R290/3	R290/3	R290/3
Defrost	Time	Time	Time	Time
External dimensions (LxDxH) (mm)	1035x850x1505	1270x850x1505	1535x850x1505	1980x850x1505
TDA - Total display area (m ²)	1,43	1,65	1,89	2,29
Net volume (l)	274	342	420	547
Refrigerated shelf area (m ²)	1,15	1,44	1,77	2,30
Insulation	PUR/H2O	PUR/H2O	PUR/H2O	PUR/H2O
Nominal power (W)	370	372	376	381
Electric current (A)	2,01	2,02	2,04	2,07
TEC - Total energy consumption (kWh/24h)	2,712	2,959	3,226	3,673
AEC - Annual energy consumption (kWh/annum)	989,88	1080,04	1177,49	1340,65
Energy efficiency class*				

* The information presented regarding the energy class (Energy Labeling regulation and Eco Design regulation) is only related to the standard models. For the energy class of the equipments with different options that involve elements of energy consumption and/or changes in the construction of the unit, please contact the manufacturer directly.

** Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

