



STANDARD

Display area in skinplate | Exterior decoration in skinplate | Worktop in skinplate | Polyurethane injected sides | Refrigerated storage | Multiplexible | Ventilated refrigeration | Digital thermometer | Electronic temperature controller | Programmable automatic defrosting | Electric evaporation of defrost water | Tempered glasses | Adjustable feet

OPTIONS

Worktop in AISI 304 stainless steel | Quartz worktop | Display area in painted plate (RAL) | Display area in AISI 304 stainless steel | Exterior decoration in painted plate (RAL) | Exterior decoration in AISI 304 stainless steel | Treated evaporator | Reversible fan motors | Refrigerated storage with drawer system | Additional socket | Joining kit | Castors with brakes | Adjustable stainless steel high feet | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



0/4 °C



Automatic



LED



230V | 1 Ph | 50 Hz



M2 | 25 °C | 60% H.R.



Plug-in



R290 ECO Friendly

| M100 SS | 150 | 200 | 250 |
|--|---------------|---------------|---------------|
| Operating temperature | 0/4 °C | 0/4 °C | 0/4 °C |
| Refrigerant (ref/GWP) | R290/3 | R290/3 | R290/3 |
| Defrost | Time | Time | Time |
| External dimensions (LxDxH) (mm) | 1525x1100x881 | 1970x1100x881 | 2570x1100x881 |
| TDA - Total display area (m ²) | 1,54 | 1,96 | 2,52 |
| Net volume (l) | 262 | 343 | 452 |
| Refrigerated shelf area (m ²) | 1,17 | 1,53 | 2,02 |
| Insulation | PUR/H2O | PUR/H2O | PUR/H2O |
| Nominal power (W) | 1075 | 1087 | 1390 |
| Electric current (A) | 5,38 | 5,41 | 6,97 |

* Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

