



STANDARD

Display area in skinplate | Exterior decoration in skinplate | Worktop in skinplate | Polyurethane injected sides | Middle shelf without lighting | Refrigerated storage | Multiplexible | Ventilated refrigeration | Sliding rear doors | LED lighting | Digital thermometer | Front glass anti-condensation system | Electronic temperature controller | Programmable automatic defrosting | Electric evaporation of defrost water | Tilting front glass | Tempered glasses | Adjustable feet

OPTIONS

Worktop in AISI 304 stainless steel | Quartz worktop | Display area in painted plate (RAL) | Display area in AISI 304 stainless steel | Exterior decoration in painted plate (RAL) | Exterior decoration in AISI 304 stainless steel | Treated evaporator | Reversible fan motors | LED lighting in ambient shelf | Supplementary shelves level without lighting | Supplementary shelves level with lighting | Refrigerated storage with drawer system | Additional socket | Joining kit | Castors with brakes | Adjustable stainless steel high feet | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



0/4 °C



Automatic



LED



230V | 1 Ph | 50 Hz



M1 | 25 °C | 60% R.H.



Plug-in



R290 ECO Friendly

M101 VD	150	200	250
Operating temperature	0/4 °C	0/4 °C	0/4 °C
Refrigerant (ref/GWP)	R290/3	R290/3	R290/3
Defrost	Time	Time	Time
External dimensions (LxDxH) (mm)	1545x1101x1201	1990x1101x1201	2590x1101x1201
TDA - Total display area (m ²)	1,18	1,48	1,89
Net volume (l)	262	343	452
Refrigerated shelf area (m ²)	1,17	1,53	2,02
Insulation	PUR/H2O	PUR/H2O	PUR/H2O
Nominal power (W)	1075	1087	1390
Electric current (A)	5,38	5,41	6,97

* Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

