



STANDARD

Exterior decoration in lacquered MDF (RAL) | Worktop in skinplate | Middle shelf without lighting | Refrigerated storage | Multiplexible | Ventilated refrigeration | Sliding rear doors | LED lighting | Digital thermometer | Front glass anti-condensation system | Electronic temperature controller | Programmable automatic defrosting | Electric evaporation of defrost water | Tilting front glass | Tempered glasses | Adjustable feet

OPTIONS

Worktop in AISI 304 stainless steel | Quartz worktop | Display area in painted plate (RAL) | Display area in AISI 304 stainless steel | Treated evaporator | Reversible fan motors | LED lighting in ambient shelf | Supplementary shelves level without lighting | Supplementary shelves level with lighting | Refrigerated storage with drawer system | Additional socket | Joining kit | Castors with brakes | Adjustable stainless steel high feet | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



0/4 °C



Automatic



LED



230V | 1 Ph | 50 Hz



M1 | 25 °C | 60% R.H.



Plug-in



R290 ECO Friendly

| M102 VD | 150 | 200 | 250 |
|--|----------------|----------------|----------------|
| Operating temperature | 0/4 °C | 0/4 °C | 0/4 °C |
| Refrigerant (ref/GWP) | R290/3 | R290/3 | R290/3 |
| Defrost | Time | Time | Time |
| External dimensions (LxDxH) (mm) | 1505x1100x1201 | 1950x1100x1201 | 2550x1100x1201 |
| TDA - Total display area (m ²) | 1,18 | 1,48 | 1,89 |
| Net volume (l) | 262 | 343 | 452 |
| Refrigerated shelf area (m ²) | 1,17 | 1,53 | 2,02 |
| Insulation | PUR/H2O | PUR/H2O | PUR/H2O |
| Nominal power (W) | 1075 | 1087 | 1390 |
| Electric current (A) | 5,38 | 5,41 | 6,97 |

* Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

