



STANDARD

3 levels of shelves | Display area in skinplate | Exterior decoration in lacquered MDF (RAL) | Pivoting rear door | Multiplexible | Ventilated refrigeration | LED lighting | Digital thermometer | Electronic temperature controller | Programmable automatic defrosting | Electric evaporation of defrost water | Tilting front glasses | Tempered glasses | Adjustable feet

OPTIONS

Display area in painted plate (RAL) | Display area in AISI 304 stainless steel | Treated evaporator | Front glass anti-condensation system | Additional socket | Adjustable stainless steel high feet | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



Automatic



230V | 1 Ph | 50 Hz



Plug-in



2/5°C



LED



M2 | 25°C | H.R. 60%



R290 ECO Friendly

Operating temperature (°C)	2/5°C
Refrigerant (ref/GWP)	R290/3
Defrost	Time
External dimensions (LxHxD) (mm)	1894x1375x2259
TDA (m ²)	2,54
Net volume (l)	451
Refrigerated shelf area (m ²)	3,24
Insulation	PUR/H2O
Nominal power (W)	1248
Electric current (A)	5,98

**Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

