



STANDARD

1 level of removable, adjustable, and tiltable shelf | Display area in skinplate | Exterior decoration in lacquered MDF (RAL) | Sliding rear doors | Multiplexible | Ventilated refrigeration | LED lighting | Digital thermometer | Electronic temperature controller | Programmable automatic defrosting | Electric evaporation of defrost water | Tilting front glass | Tempered glasses | Double-glass sides | Adjustable feet

OPTIONS

Display area in painted plate (RAL) | Display area in AISI 304 stainless steel | Treated evaporator | Front glass anti-condensation system | Additional socket | Castors with brakes | Adjustable stainless steel high feet | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



2/5 °C



Automatic



LED



230V | 1 Ph | 50 Hz



M2 | 25 °C | 60% H.R.




Plug-in



R290 ECO Friendly

P082 VD H115**130**

Operating temperature	2/5 °C
Refrigerant (ref/GWP)	R290/3
Defrost	Time
External dimensions (LxDxH) (mm)	1295x860x1150
TDA - Total display area (m ²)	2,12
Net volume (l)	285
Refrigerated shelf area (m ²)	1,27
Insulation	PUR/H2O
Nominal power (W)	1140
Electric current (A)	5,74
TEC - Total energy consumption (kWh/24h)	11,929
AEC - Annual energy consumption (kWh/annum)	4354,09
Energy efficiency class*	

* The information presented regarding the energy class (Energy Labeling regulation and Eco Design regulation) is only related to the standard models. For the energy class of the equipments with different options that involve elements of energy consumption and/or changes in the construction of the unit, please contact the manufacturer directly.

** Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

