



## STANDARD

3 levels of removable, adjustable, and tiltable shelves | Display area in AISI 304 stainless steel | Exterior decoration in lacquered MDF (RAL) | Sliding rear doors | Multiplexible | Ventilated heating | LED lighting | Digital thermometer | Electronic temperature controller | Safety thermostat | Tilting front double glass | Tempered glasses | Double-glass sides

## OPTIONS

Display area in painted plate (RAL) | Display area in AISI 304 stainless steel | Castors with brakes | Adjustable stainless steel high feet | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



Automatic



230V | 1 Ph | 50 Hz



Plug-in



65/75°C



LED



M2 | 25°C | H.R. 60%



R290 ECO Friendly

P082 VD H	100	130	150
Operating temperature (°C)	65/75°C	65/75°C	65/75°C
System	Ventilated	Ventilated	Ventilated
Length without sides (mm)	945	1245	1445
External dimensions (LxHxD) (mm)	1025x1371x869	1326x1371x869	1525x1371x869
TDA (m <sup>2</sup> )	1,57	1,85	2,04
Net volume (l)	277	367	426
Refrigerated shelf area (m <sup>2</sup> )	1,65	2,18	2,54
Insulation	PUR/H2O	PUR/H2O	PUR/H2O
Nominal power (W)	1248	1501	2025
Electric current (A)	4,84	6,82	9,19

\*\*Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

