



STANDARD

3 levels of removable, adjustable, and tiltable shelves | Display area in AISI 304 stainless steel | Exterior decoration in lacquered MDF (RAL) | Sliding rear doors | Multiplexible | Ventilated heating | LED lighting | Digital thermometer | Electronic temperature controller | Safety thermostat | Tilting front double glass | Tempered glasses | Double-glass sides

OPTIONS

Display area in painted plate (RAL) | Display area in AISI 304 stainless steel | Castors with brakes | Adjustable stainless steel high feet | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilé



Automatique



230V | 1 Ph | 50 Hz



Plug-in



65/75°C



LED



M2 | 25°C | H.R. 60%



R290 ECO Friendly

P082 VD H	100	130	150
Température de fonctionnement (°C)	65/75°C	65/75°C	65/75°C
Système	Ventilé	Ventilé	Ventilé
Longueur sans joues (mm)	945	1245	1445
Dimensions extérieures (LxHxP) (mm)	1025x1371x869	1326x1371x869	1525x1371x869
TDA (m²)	1,57	1,85	2,04
Volume net (l)	277	367	426
Surface d'étagère réfrigérée (m²)	1,65	2,18	2,54
Isolation	PUR/H2O	PUR/H2O	PUR/H2O
Puissance électrique (W)	1248	1501	2025
Courant (A)	4,84	6,82	9,19

**Images et couleurs non contractuelles. L'information présentée concerne l'équipement standard avec froid incorporé. Pour obtenir les informations pour froid à distance ou vitrine neutre, contactez le fabricant.

