



STANDARD

6 levels of removable shelves | Self-closing hinged front doors with double tempered glass | Interior and exterior in skinplate | Skinplate product stopper | Solid sides | Ventilated refrigeration | Vertical LED lighting | Electronic temperature controller | Programmable automatic defrosting | Adjustable feet | Fixation kit

OPTIONS

Display area in painted plate (RAL) | Display area in AISI 304 stainless steel | Exterior decoration in painted plate (RAL) | Exterior decoration in AISI 304 stainless steel | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



0/4 °C



Automatic



LED



230V | 1 Ph | 50 Hz



M1 | 25 °C | 60% R.H.




Plug-in



R290 ECO Friendly

SLENDER PT

80

Operating temperature	0/4 °C
Refrigerant (ref/GWP)	R290/3
Defrost	Time
External dimensions (LxDxH) (mm)	800x392x2213
TDA - Total display area (m ²)	0,87
Net volume (l)	88
Refrigerated shelf area (m ²)	0,59
Insulation	PUR/H2O
Nominal power (W)	626
Electric current (A)	3,03
TEC - Total energy consumption (kWh/24h)	10,314
AEC - Annual energy consumption (kWh/annum)	3764,61
Energy efficiency class*	

* The information presented regarding the energy class (Energy Labeling regulation and Eco Design regulation) is only related to the standard models. For the energy class of the equipments with different options that involve elements of energy consumption and/or changes in the construction of the unit, please contact the manufacturer directly.

** Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

