



## STANDARD

2 levels of removable shelves | Acrylic hinged door | Interior in skinplate | Collapsible equipment | Exterior in polystyrene | Ventilated refrigeration | Vertical LED lighting | Electronic temperature controller | Programmable automatic defrosting | Automatic evaporation of defrost water | Castors

## OPTIONS

Display area in painted plate (RAL) | Exterior decoration in painted plate (RAL) | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



0/4 °C



Automatic



LED



230V | 1 Ph | 50 Hz



M2 | 25 °C | 60% R.H.




Plug-in



R290 ECO Friendly

TANGRAM PT

50

Operating temperature	0/4 °C
Refrigerant (ref/GWP)	R290/3
Defrost	Time
External dimensions (LxDxH) (mm)	474x507x1274
TDA - Total display area (m <sup>2</sup> )	0,24
Net volume (l)	73
Refrigerated shelf area (m <sup>2</sup> )	0,36
Insulation	PUR/H2O
Nominal power (W)	664
Electric current (A)	3,45
TEC - Total energy consumption (kWh/24h)	7,841
AEC - Annual energy consumption (kWh/annum)	2861,97
Energy efficiency class*	

\* The information presented regarding the energy class (Energy Labeling regulation and Eco Design regulation) is only related to the standard models. For the energy class of the equipments with different options that involve elements of energy consumption and/or changes in the construction of the unit, please contact the manufacturer directly.  
 \*\* Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

