



STANDARD

4 levels of removable, adjustable, and tiltable shelves | Display area in skinplate | Exterior decoration in skinplate | Display sides with double tempered glass | Multiplexible | Ventilated refrigeration | LED top lighting | Electronic temperature controller | Programmable automatic defrosting | Electric evaporation of defrost water | Adjustable feet | Night curtain

OPTIONS

Upper sling bar for hooks | Display area in painted plate (RAL) | Display area in AISI 304 stainless steel | Exterior decoration in painted plate (RAL) | Exterior decoration in AISI 304 stainless steel | Treated evaporator | LED lighting on shelves | Solid sides | Panoramic sides | Supplementary shelves level without lighting | Supplementary shelves level with lighting | Joining kit | Castors with brakes | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



2/5 °C



Automatic



LED



230V | 1 Ph | 50 Hz



M2 | 25 °C | 60% H.R.



Plug-in



R290 ECO Friendly

W060 SS	100	130	150	250	300
Operating temperature	2/5 °C	2/5 °C	2/5 °C	2/5 °C	2/5 °C
Refrigerant (ref/GWP)	R290/3	R290/3	R290/3	R290/3	R290/3
Defrost	Time	Time	Time	Time	Time
External dimensions (LxDxH) (mm)	1037x610x1952	1272x610x1952	1537x610x1952	2452x610x1952	2982x610x1952
TDA - Total display area (m ²)	1,38	1,68	2,03	3,25	3,95
Net volume (l)	283	353	432	706	864
Refrigerated shelf area (m ²)	1,4	1,75	2,14	3,5	4,28
Insulation	PUR/H2O	PUR/H2O	PUR/H2O	PUR/H2O	PUR/H2O
Nominal power (W)	1611	1636	2556	3272	5112
Electric current (A)	7,9	8,1	13,3	16,3	26,6
TEC - Total energy consumption (kWh/24h)	13,593	15,624	17,729	30,333	35,374
AEC - Annual energy consumption (kWh/annum)	4961,45	5702,76	6471,09	11071,55	12911,51
Energy efficiency class*					

* The information presented regarding the energy class (Energy Labeling regulation and Eco Design regulation) is only related to the standard models. For the energy class of the equipments with different options that involve elements of energy consumption and/or changes in the construction of the unit, please contact the manufacturer directly.

** Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

