



STANDARD

4 levels of removable, adjustable, and tilttable shelves | Front sliding doors with double tempered glass | Display area in skinplate | Exterior decoration in skinplate | Display sides with double tempered glass | Multiplexible | Ventilated refrigeration | LED vertical lighting | Electronic temperature controller | Programmable automatic defrosting | Automatic evaporation of defrost water | Adjustable feet

OPTIONS

Upper sling bar for hooks | Display area in painted plate (RAL) | Display area in AISI 304 stainless steel | Exterior decoration in painted plate (RAL) | Exterior decoration in AISI 304 stainless steel | Treated evaporator | LED lighting on shelves | Solid sides | Panoramic sides | Supplementary shelves level without lighting | Supplementary shelves level with lighting | Joining kit | Castors with brakes | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



0/4 °C



Automatic



LED



230V | 1 Ph | 50 Hz



M1 | 25 °C | 60% R.H.



Plug-in



R290 ECO Friendly

W080 PC	100	130	150	200	250	300
Operating temperature	0/4 °C	0/4 °C	0/4 °C	0/4 °C	0/4 °C	0/4 °C
Refrigerant (ref/GWP)	R290/3	R290/3	R290/3	R290/3	R290/3	R290/3
Defrost	Time	Time	Time	Time	Time	Time
External dimensions (LxDxH) (mm)	1037x819x1952	1272x819x1952	1537x819x1952	1982x819x1952	2452x819x1952	2982x819x1952
TDA - Total display area (m ²)	1,20	1,47	1,71	2,23	2,70	3,18
Net volume (l)	426	532	651	851	1062	1300
Refrigerated shelf area (m ²)	2,13	2,65	3,25	4,25	5,31	6,51
Insulation	PUR/H2O	PUR/H2O	PUR/H2O	PUR/H2O	PUR/H2O	PUR/H2O
Nominal power (W)	988	1002	514	736	1504	1528
Electric current (A)	4,86	4,92	2,97	3,65	7,67	9,47
TEC - Total energy consumption (kWh/24h)	5,654	6,586	7,400	9,474	13,172	14,800
AEC - Annual energy consumption (kWh/annum)	2063,71	2403,89	2701,00	3458,01	4807,78	5402,00
Energy efficiency class*						

* The information presented regarding the energy class (Energy Labeling regulation and Eco Design regulation) is only related to the standard models. For the energy class of the equipments with different options that involve elements of energy consumption and/or changes in the construction of the unit, please contact the manufacturer directly.

** Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

