



STANDARD

3 levels of removable, adjustable, and tiltable shelves | Display area in skinplate | Exterior decoration in lacquered MDF (RAL) | Sliding rear doors | Multiplexible | Ventilated refrigeration | LED lighting | Digital thermometer | Electronic temperature controller | Programmable automatic defrosting | Electric evaporation of defrost water | Tilting front glass | Tempered glasses | Double-glass sides | Adjustable feet

OPTIONS

Display area in painted plate (RAL) | Display area in AISI 304 stainless steel | Treated evaporator | Front glass anti-condensation system | Additional socket | Castors with brakes | Adjustable stainless steel high feet | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



Automatic



230V | 1 Ph | 50 Hz



Plug-in



2/5°C



LED



M2 | 25°C | H.R. 60%



R290 ECO Friendly

P082 VD	100	130	150	200
Operating temperature (°C)	2/5°C	2/5°C	2/5°C	2/5°C
Refrigerant (ref/GWP)	R290/3	R290/3	R290/3	R290/3
Defrost	Time	Time	Time	Time
Length without sides (mm)	945	1245	1445	1890
External dimensions (LxHxD) (mm)	1025x1371x869	1325x1371x869	1525x1371x869	1970x1371x869
TDA (m ²)	1,57	1,85	2,04	2,47
Net volume (l)	277	367	426	589
Refrigerated shelf area (m ²)	1,65	2,18	2,54	3,57
Insulation	PUR/H2O	PUR/H2O	PUR/H2O	PUR/H2O
Nominal power (W)	1212	1248	1643	1666
Electric current (A)	5,8	5,98	7,35	8,03
Total energy consumption (kWh/24h)	10,340	12,557	13,937	19,594
Annual energy consumption (kWh/annum)	3774,10	4583,31	5087,01	7151,81
Energy efficiency class*				

*The information presented regarding the energy class (Energy Labeling regulation and Eco Design regulation) is only related to the standard models. For the energy class of the equipments with different options that involve elements of energy consumption and/or changes in the construction of the unit, please contact the manufacturer directly

**Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

